

The Creonic CCSDS AR4JA LDPC IP support the LDPC coding schemes as defined by the CCSDS standard. The LDPC codes with rates 1/2, 2/3 and 4/5, block lengths 1024, 4096 and 16384 are specially designed for deep-space missions, but the excellent error correction performance makes it the ideal fit for further applications with highest demands on forward error correction. The IP cores are available for ASIC and FPGAs (AMD Xilinx, Intel, Microchip).

## CCSDS AR4JA LDPC Decoder

Key benefits of the decoder are:

- Gains of up to 3 dB compared to Viterbi decoders.
- Low-power and low-complexity design.
- Layered LDPC decoder architecture, for convergence behavior that is twice as fast as non-layered LDPC decoders
- Early stopping criterion for iterative LDPC decoder, saving a considerable amount of energy.
- Optional fixed number of iterations for fixed latency of blocks with the same code rate and block length.
- Configurable amount of LDPC decoding iterations for trading-off throughput and error correction performance.
- Collection of statistic information (number of iterations, decoding success, number of modified bits).

## CCSDS AR4JA LDPC Encoder

Key benefits of the encoder are:

- High-throughput, low-latency encoder core.
- Low-power and low-complexity design.

## Performance Figures

- Encoder payload throughput of up to 100 Mbit/s at 200 MHz
- Decoder payload throughput of up to more than 100 Mbit/s (30 iterations, 200 MHz)



## Features

- Support for code rates 1/2, 2/3, and 4/5
- Uncoded block sizes of 1024, 4096, and 16384 bits
- Compliant with “TM Synchronization and Channel Coding, Recommended Standard, CCSDS 131.0-B-3, Blue Book, September 2017”.

## Applications

- Near-Earth and Deep-Space communication.
- Space links communication.
- Space internet-working services.
- Further High-performance Applications

## Deliverables

- VHDL source code or synthesized netlist with testbench
- HDL and Bit-accurate Matlab, C or C++ simulation models
- Vivado IP Package
- Comprehensive documentation

## Error Correction Performance

The following table shows bit error rate (BER) and block error rate (BLER) of the CCSDS AR4JA LDPC decoder.

Code Rate	Block length (k)	BER 10 <sup>-6</sup>	E <sub>b</sub> /N <sub>0</sub> (dB) at	
			BER 10 <sup>-7</sup>	BLER 10 <sup>-5</sup>
1/2	1024	2.20	2.30	2.20
1/2	4096	1.60	1.65	1.60
1/2	16384	1.30	1.35	1.35
2/3	1024	2.95	3.10	3.00
2/3	4096	2.35	2.40	2.35
2/3	16384	2.05	2.10	2.05
4/5	1024	3.95	4.10	4.20
4/5	4096	3.20	3.25	3.25
4/5	16384	2.85	2.90	2.90

Error correction performance of the CCSDS AR4JA decoder at 31 iterations and 6 bit input.

## Related Products

[CCSDS LDPC Decoder](#)

[CCSDS SCCC Turbo Encoder and Decoder](#)

[DVB-S2X LDPC/BCH Decoder](#)

[DVB-RCS2 Turbo Decoder](#)

## About Creonic

Creonic is an ISO 9001:2015 certified provider of ready-for-use IP cores for wired, wireless, fiber, and free-space optical communications. All relevant digital signal processing algorithms are covered, including, but not limited to, forward error correction, modulation, equalization, and demodulation. The company offers the richest product portfolio in this field, covering standards like 3GPP 5G, DVB-S2X, DVB-RCS2, CCSDS, and WiFi. The products are applicable for ASIC and FPGA technologies and comply with the highest requirements with respect to quality and performance. For more information please visit our website at [www.creonic.com](http://www.creonic.com).

## Contact

Creonic GmbH  
 Bahnhofstr. 26-28  
 67655 Kaiserslautern  
 Germany

Phone: +49 631 3435 9880  
 Fax: +49 631 3435 9889  
 Web: [www.creonic.com](http://www.creonic.com)  
 E-mail: [sales@creonic.com](mailto:sales@creonic.com)

LinkedIn: [Creonic](#)  
 Facebook: [Creonic](#)