

DVB-RCS (Digital Video Broadcast - Interaction channel for satellite distribution systems) is an established ETSI standard for digital data transmission via satellites. It uses an 8-state double-binary turbo decoder that has an excellent error correction performance. This outstanding performance of the DVB-RCS turbo decoder makes it the ideal candidate for further applications where high spectral efficiency is key for lowering costs.

Benefits

- Gains up to 4 dB compared to convolutional codes.
- Design-time configuration of throughput, input bit widths, and maximum block length for optimal resource utilization.
- Low-power and low-complexity design.
- Burst-to-burst on-the-fly configuration.
- Configurable interleaver parameters allow for support of custom block lengths.
- On-the-fly bit error rate measurement.
- High block length and code rate granularity.
- Configurable amount of turbo decoder iterations for trading-off throughput and error correction performance.
- Allows for easy migration from legacy DVB-RCS turbo decoders.
- Allows for turbo synchronization to further improve error correction performance (on request).
- Available for ASIC and FPGAs (AMD Xilinx, Intel).

Performance Figures

- Payload throughput of up to 131 Mbit/s at 5 iterations and 82 Mbit/s at 8 iterations (200 MHz).
- BLER 10^{-5} with code rate 3/4 at
 - $E_S/N_0 = 6.1$ dB (QPSK, 53 payload bytes)
 - $E_S/N_0 = 5.2$ dB (QPSK, 212 payload bytes)



Features

- Compliant with ETSI 301 790 V1.4.1 (2005-09) (DVB-RCS)
- Support for all DVB-RCS payload block sizes (12 to 216 bytes) and code rates (1/3 to 6/7)
- Support for QPSK and 8-PSK modulation interfaces

Applications

- Satellite communication
 - Interactive Services
 - Professional Services
 - TDMA
- Applications with the highest demands on forward error correction
- Applications with the need for a wide range of code rates (1/3 and above) and block lengths

Deliverables

- VHDL source code or synthesized netlist
- HDL simulation models e.g. for Aldec's Riviera-PRO
- VHDL testbench
- bit-accurate Matlab, C or C++ simulation model
- comprehensive documentation

Related Products

[DVB-RCS2 Turbo Decoder](#)

[DVB-S2 LDPC/BCH Encoder and Decoder](#)

[GEO-Mobile Radio LDPC Decoder](#)

[DVB-C2 LDPC/BCH Decoder](#)

[802.11n/ac LDPC Decoder](#)

About Creonic

Creonic is an ISO 9001:2015 certified provider of ready-for-use IP cores for wired, wireless, fiber, and free-space optical communications. All relevant digital signal processing algorithms are covered, including, but not limited to, forward error correction, modulation, equalization, and demodulation. The company offers the richest product portfolio in this field, covering standards like 3GPP 5G, DVB-S2X, DVB-RCS2, CCSDS, and WiFi. The products are applicable for ASIC and FPGA technologies and comply with the highest requirements with respect to quality and performance. For more information please visit our website at www.creonic.com.

Contact

Creonic GmbH
Bahnhofstr. 26-28
67655 Kaiserslautern
Germany

Phone: +49 631 3435 9880
Fax: +49 631 3435 9889
Web: www.creonic.com
E-mail: sales@creonic.com

Twitter: [Creonic_IPCores](#)
Facebook: [Creonic](#)
LinkedIn: [Creonic](#)
